

Costco

Variety	Packaging	Pack Style	Weight	Size	Min. Color	Pressure	Grade	Packed Date	Costco Item #	UPC Code	GTIN (Box)
Fuji	Yes! Apple/Costco Box	4lb Box	4lb w/out the box	2.81" min. - 3.52" max	50%	14	XF	YES	7947	879329008482	10879329008489
Gala					50%	14			5851	879329008475	10879329008472
Honeycrisp					50%	11			6659	879329008499	10879329008496
RubyFrost®	Club Variety Box				See SD/RF Packer Specs				3862	879329008529	10879329008557
SnapDragon®	Club Variety Box				3806	879329008512			10879329008519		
SweeTango®	Club Variety Box				50%	12			3891	879329008543	10879329008540

*Shrink-wrap the pallets from top to bottom, include wrapping the pallet to ensure that product is secure. Add corner boards.

*Max days from Pack Date: 40

*Acceptable temperature range = 32 to 45F Aug-Nov = 32 to 55F

*Master case must include **Pack Date** Ex. Jan 1, 2021 or 1 Jan 2021

*Sell units must have traceability information printed on the sell unit

*Sell units must have item number and UPC/Barcode listed on the sell unit

*The sticker on master case must be on the lower right hand corner of the display side of the box if possible

*UPCs must not face the open side of the master case

*Case weight 36lbs

Approved temperature recorders:



Additional PDFs Online:

*Temperature Recorder


*Packaging Specs

#5851 4LB GALA

VALID 11/2022 - 9/2023 Last revised

2-Nov-22

REASON TO REFUSE



Less than 40% Coloring
Allowable tolerance of 5%



Stem Bowl Cracks
Allowable tolerance of 5%



Longitudinal Russet
Allowable tolerance of 5%



Internal Mold
ZERO TOLERANCE

Cut open to inspect for browning & internal mold

REASON TO REFUSE



Mechanical Damage
Allowable tolerance of 5%



Puncture Marks
Allowable tolerance of 5%



Internal Browning
Zero Tolerance

Additional information




FULL GALA COLORING



80 % GALA COLORING

REASON TO REFUSE



Less than 40% Coloring



SCALD - ZERO TOLERANCE



BITTER PIT - ZERO TOLERANCE

REASON TO REFUSE



Shoulder Cracking
Allowable tolerance of 5%



Insect Damage
Allowable tolerance of 5%



Internal Browning
ZERO TOLERANCE



Internal Mold
ZERO TOLERANCE

Cut open to inspect for browning & internal mold

Additional information



40% Red Minimum




80% Red Minimum

REASON TO REFUSE



Flecking - 40% or Greater
Allowable tolerance of 5%



Internal Browning
Zero Tolerance



Russeting
Zero Tolerance

Cut open to inspect for browning & internal mold



Internal Mold
Zero tolerance

REASON TO REFUSE



30 % or lower in coloring - **TOO LIGHT**
5 % of the samples taken



50 % or lower in coloring - **TOO LIGHT**
Avoid the yellow/green color of Fujis that are too light
Unlike Gala, High Red Fujis are welcome

Additional information

- * No more than 2 bad apples taken from 6 samples throughout the load for under pressure
- * Up to 20% maximum tolerance of connected watercore star 1.5 inches to 2.0 inches in diameter. Descriptive photo set below:



"Water Core "up" to 1.5" across is OKAY "



70 % in Coloring & higher - Approved

Reasons to refuse



Less than 40% Coloring



SCALD
Zero Tolerance



BITTER PIT
Zero Tolerance

Reasons to refuse




Heat Stress
Allowable tolerance of 2%



Shoulder Cracking
Allowable tolerance of 2%



Internal Browning
Zero tolerance



Internal Mold
Zero tolerance

Cut open to inspect for browning & internal mold

Additional information




80 % & above Red Color



60 % Red Minimum Color

REASON TO REFUSE



Less than 40% Coloring



SCALD - ZERO TOLERANCE



BITTER PIT - ZERO TOLERANCE

REASON TO REFUSE



Shoulder Cracking
Allowable tolerance of 5%



Insect Damage
Allowable tolerance of 5%



Internal Browning
Zero Tolerance



Internal Mold
Zero Tolerance

Cut open to inspect for browning & internal mold

Additional information



40% Red Minimum



80% Red Minimum

Reasons to refuse



Less than 40% Coloring



SCALD
Zero Tolerance



BITTER PIT
Zero Tolerance

Reasons to refuse



Heat Stress
Zero Tolerance



Shoulder Cracking
Allowable tolerance of 5%



Internal Browning
Zero Tolerance



Internal Mold
Zero Tolerance

Cut open to inspect for browning & internal mold

Additional information



80 % & above Red Color



60 % Red Minimum Color